

5ELEN018W - Robotic Principles  
Lecture 2: Introduction to Robotics -  
Configuration Space


Dr Dimitris C. Dracopoulos

# Before Robots

Fascination for mechanical devices such as automata. Complex enough (for that time) to demonstrate some kind of life-like behaviour.

**Example:** Vaucanson's Digesting Duck (1739)

- ▶ Flap its wings, eat grain and defecate.



## History and Terminology

The word *robot* comes from the word *Robota* in Slav languages, first introduced by the Czech playwright Karel Capek in his play *Rossum's Universal Robots* (RUR) in 1920.



The original word meaning was *worker*.

Free audiobook:

[https://archive.org/details/rossums\\_universal\\_robots\\_1409\\_librivox](https://archive.org/details/rossums_universal_robots_1409_librivox)

# History and Terminology (cont'd)

Robots in many:

- ▶ Science fiction books
- ▶ Movies

In the mid twentieth century (1950s), the term *cybernetics* was used for an exciting science field to understand life and create intelligent machines.

# The 3 Laws of Robotics — Isaac Asimov

1. A robot may not injure a human being or, through inaction, allow a human being to come to harm.
2. A robot must obey orders given it by human beings except where such orders would conflict with the First Law.
3. A robot must protect its own existence as long as such protection does not conflict with the First or Second Law.

# Videos on the history of Robots

- ▶ Robots - A 50 year journey video
- ▶ Robots - The journey continues video

# Robots Today

Robotic automation mostly used in Manufacturing (millions of arm-type robots), e.g.:

- ▶ Welding
- ▶ Painting
- ▶ Machine loading/unloading
- ▶ Electronic assembly
- ▶ Packaging

# Categorising Robots and Definition

Many different ways to classify robots, e.g.

- ▶ Fixed in place.
- ▶ Mobile (legs, wheels, wings, etc)

or according to the operation they perform:

- ▶ Manufacturing
- ▶ Service robots (cleaning, personal care, medical)
- ▶ Field robots (agriculture, mining, construction)
- ▶ Humanoid robots having the form of a human being and perform more than one tasks

A robot can be defined as (according to Peter Corke):

*A goal oriented machine that can sense, plan and act.*



# Characteristics of Robots

- ▶ Consistent
- ▶ Accurate
- ▶ Reliable

Do things that people

- ▶ can't do
  - space, deep sea
- ▶ won't do
  - dull, boring tasks
- ▶ shouldn't do
  - dangerous, unhealthy, risky

# Rigid Bodies and Robotic Manipulators

The most common form of an industrial robot is a **mechanical manipulator**.

- ▶ A mechanical manipulator consists of rigid bodies (called *links*) connected by *joints*.
- ▶ The joints are moved by actuators (e.g. electric motors).
- ▶ An *end-effector* (gripper or hand) is usually attached to a specific link.

A *rigid body* is a solid body which cannot be deformed (or deformations are so small that can be neglected). The distance between any 2 points in a rigid body remains constant even if forces are applied.

# A Modern Robotic Manipulator





Image courtesy KUKA Roboter GmbH.

- ▶ The above has 7 degrees of freedom as explained a bit later.

# Robotic Manipulators and Configuration Space



- ▶ How can we specify the exact position of a Robot (Manipulator)?

# Configuration Space


The answer to How can we specify the exact position of a Robot is:

- ▶ **Robot Configuration:** a specification of the positions of ALL points of a robot.


Robot links are rigid: therefore only a few numbers are required to represent its configuration (position).

# Configuration Examples

- ▶ *How can the configuration of a door be represented?*  
→ angle  $\theta$  about its hinge.




- ▶ *How can the configuration of a point on a plane be described?*  
→ 2 coordinates  $(x, y)$



## Configuration Examples (cont'd)

- ▶ *How can the configuration of a coin lying on a table be represented?*
  - 2 coordinates  $(x, y)$  to specify the position of a fixed point on the coin (e.g. centre) and one coordinate  $\theta$  to specify the coin's orientation.



# Degrees of Freedom of a Body (Robot)

The number of **degrees of freedom (DOF)** of a body (e.g. robot) is the smallest number of real-valued variables needed to represent its configuration.


- ▶ **C-space (Configuration space)**: the  $n$ -dimensional space of all possible configurations of a robot
- ▶ Degrees of freedom  $n$  is the dimension of the *C-space*



# Degrees of Freedom of a Spatial Rigid Body

A rigid body in a 3-dimensional space (*spatial rigid body*) has 6 degrees of freedom.

- ▶  $(x, y, z)$  coordinates for specifying the position of the centre of mass.
- ▶ 3 angles  $(\theta, \phi, \psi)$  specifying the orientation (attitude) of the body.





<https://compsci290-s2016.github.io/CoursePage/Materials/EulerAnglesViz/>

# Degrees of Freedom for Robots

$$\text{degrees of freedom} = (\text{sum of freedoms of the bodies}) - (\text{number of independent constraints}) \quad (1)$$

# Types of Robot Joints



# Robot Joints: Degrees of Freedom and Constraints

- ▶ A joint provides freedoms to allow one rigid body to move relative to another
- ▶ *Equivalently*: a joint provides constraints on the possible motions of 2 rigid bodies it connects.

Joint type	dof $f$	Constraints $c$ between two planar rigid bodies	Constraints $c$ between two spatial rigid bodies
Revolute (R)	1	2	5
Prismatic (P)	1	2	5
Helical (H)	1	N/A	5
Cylindrical (C)	2	N/A	4
Universal (U)	2	N/A	4
Spherical (S)	3	N/A	3

- ▶ *The number of degrees of freedom of a rigid body (3 for planar bodies, 6 for spatial bodies) minus the number of constraints provided by a joint, must equal the number of freedoms provided by that joint.*

## Grübler's Formula

The number of degrees of freedom of a mechanism (robot) with links and joints can be calculated using *Grübler's formula* which is another expression of equation (1).

Consider a mechanism (robot) with:

- ▶  $N$  links (ground is also considered a link)
- ▶  $J$  joints
- ▶  $m$  is the degrees of freedom of a rigid body ( $m = 3$  for planar mechanisms,  $m = 6$  for spatial mechanisms)
- ▶  $f_i$  the number of freedoms provided by joint  $i$
- ▶  $c_i$  the number of constraints provided by joint  $i$ , where  $f_i + c_i = m$  for all joints  $i$ .

**assumes all joints constraints are independent.**

Then:


$$\text{dof} = m \cdot (N - 1 - J) + \sum_{i=1}^J f_i \quad (2)$$

## Derivation of Grübler's Formula

$$\begin{aligned} \text{dof} &= \underbrace{m \cdot (N - 1)}_{\text{rigid body freedoms}} - \underbrace{\sum_{i=1}^J c_i}_{\text{joint constraints}} \\ &= m \cdot (N - 1) - \sum_{i=1}^J (m - f_i) \\ &= m \cdot (N - 1) - \sum_{i=1}^J m + \sum_{i=1}^J f_i \\ &= m \cdot (N - 1 - J) + \sum_{i=1}^J f_i \end{aligned} \quad (3)$$

## Example of Grübler's Formula - Open Chain

3R Serial (3 revolute)




- ▶  $m = 3$  (planar)
- ▶  $J = 4$
- ▶  $N = 5$  (including the ground)
- ▶  $f_i = 1$

$$\text{dof} = 3(5 - 1 - 4) + 4 = 4 \quad (4)$$

# Example of Grübler's Formula - Closed Chain mechanism

## Four-Bar Linkage




- ▶  $m = 3$  (planar)
- ▶  $J = 4$
- ▶  $N = 4$  (including the ground)
- ▶  $f_i = 1$

$$\text{dof} = 3(4 - 1 - 4) + 4 = 1 \quad (5)$$



## Example of Grübler's Formula - Slider-crank mechanism



3 revolute joints and 1 prismatic joint.


- ▶  $m = 3$  (planar)
- ▶  $J = 4$
- ▶  $N = 4$  (including the ground)
- ▶  $f_i = 1$

$$\text{dof} = 3(4 - 1 - 4) + 4 = 1 \quad (6)$$

# Coordinate Reference Frames

- ▶ Fixed to the body of the robot (moving)
- ▶ Fixed somewhere in space (stationary)


In robotics, the  $x, y, z$  axes are aligned according to the right hand rule:



# Kinematics


The science of motion that treats motion without considering the forces which cause it.

- ▶ *Forward Kinematics*: Given the angles for the joints, calculate (compute) the position and orientation of the end-effector of a robot manipulator.



## Kinematics (cont'd)

- *Inverse Kinematics*: Given the position and orientation of the end-effector, compute all possible sets of joint angles that can be used to achieve this position and orientation.



# Robots: Social Issues and Ethics

## Social Issues:

- ▶ Workers losing their jobs and income
- ▶ Economic consequences
- ▶ Legal rights of robots (as they become more advanced and intelligent)

## Ethical Issues:

- ▶ Self driving cars:
  - Choosing to save the driver over pedestrians or other drivers, etc?
  - Who is to blame, the robot, the software developer, the manufacturer or the owner of the car?
- ▶ Robotic healthcare: who to blame (surgery failure, etc.)?
- ▶ Robots looking after elderly people: is this right as their quality of life is affected by removing human contact?
- ▶ Robots looking after children?
- ▶ Using robots in armies to kill human beings?